

Section Drawing for Additions

Name: _____

Address: _____

Shingles: _____

Roof Sheathing: _____

Pre-Fab Trusses @ _____ o.c.

(OR) Rafters: _____ @ _____ o.c.

Collar Ties: _____

Ceiling Joists: _____ @ _____ o.c.

Insulation: Minimum R50

Vapour Barrier: 6 mil poly

Interior Finish: _____

Overhang: _____ in.

Exterior Finish:

Wall Sheathing:

Walls: 2 in. X _____ @ _____ o.c.

* Min. Insulation: R24 for hardy board, fiber cement and/or stucco
R22 for all other

Vapour Barrier: 6 mill poly

Interior Finish: _____

2.1 m (7 ft.) Minimum Clearance

Subfloor: _____

Floor Joists: _____ @ _____ o.c.

Bridging: _____

R22 R24
* Minimum insulation value must be the same as the wall assembly for the ground to underside of floor sheathing c/w 6 mill poly vapour barrier.

25 mm (2 in.) sand ballast on 6 mill poly vapour barrier under entire addition and existing.

4 in. clean course granular layer for future subfloor depressurization system.

Foundation Type: _____

The following documents are to be submitted with this form:

- Detailed Site Plan
- Elevation Drawing
- Foundation Drawing, and MUST be Sealed by a Structural Engineer